

Stainless Steel Oil + Solid Fuel Liner Kits

ALL FUEL APPLICATIONS

Z-FLEX® Stainless Chimney Kits

Everything you need to get the job done right.

Z-FLEX® Stainless Steel Chimney Liner Kits come complete with everything you need to quickly and easily install a professional venting system.

It is manufactured from special high temperature and acid resistant stainless steel exclusive to Z-FLEX®.

Z-FLEX®'s specially designed 'deep corrugations' provide for greater flexibility and ease of installation. The result is a clearly superior product offering incredible longevity.



Pellet, Oil & Gas Kit Includes:

- Stainless Steel Liner
- Chimney Flashing
- Rain Cap
- Mortar Collar

Part No.: 20ILKTX

Dia.: _____ | Lgth.: _____

Dia.: 3"-24" | Lengths: 50'



All Fuel Kit Includes:

- Stainless Steel Liner
- Chimney Flashing
- Rain Cap

Part No.: 2ZFLKIT

Dia.: _____ | Lgth.: _____

Dia.: 3"-24" | Lengths: 50'



All Fuel Insert Kit Includes:

- Stainless Steel Liner
- Chimney Flashing
- Rain Cap
- Dripless Connector

Part No.: 20ILKTX_I

Dia.: _____ | Lgth.: _____

Dia.: 3"-24" | Lengths: 50'



Smoothcore Kit Includes:

- Stainless Steel Liner
- Chimney Flashing
- Rain Cap

Part No.: 2ZFCKIT

Dia.: _____ | Lgth.: _____

Dia.: 3"-8" | Lengths: 50'



For Use with Natural Draft Appliances.

Not intended for use with Category II, III, or IV gas burning appliances as defined by the National Fuel Gas Code, NFPA 54, or other appliances that result in condensation or corrosive acids on the liner of the chimney, or that create positive pressures in the chimney system.



Flex Ready Lock N'Go Tee (Cleanout)

- 3pc. with removeable snout and clean out
- All stainless steel
- Fail-safe mechanical connection from snout to body

When to Z-FLEX® a Chimney

- When a masonry chimney has no liner at all
- When damage to existing chimney lining is evident
- When new burner is installed on existing equipment
- When firing rate of existing burner is reduced
- When a new appliance is connected to an existing chimney
- When the existing chimney is oversized relative to heating equipment



Stainless Steel Flex Liner

Part No.: 2ZLSSXX

Dia.: _____ | Lgth.: _____

Part No.: 2ZL294C

Dia.: _____ | Lgth.: _____

Dia.: 2" – 24"

Lengths : Up to 50' or multiples of 5'.



Rain Cap

Part No.: 2RNCAPS

Dia.: _____

Dia.: 3" – 24"



Stainless Steel Chimney Flashing

Starter Collar 16" x 16" Base

Part No.: 2ZSCSXX

Dia.: _____

Dia.: 3" – 24"



Top Support

Part No.: 2ZTSXXX

Dia.: _____

Dia.: 3" – 24"



Lock N'Go Tee

Part No.: 2ZFTXX

Dia.: _____

Dia.: 3" – 24"

Z-FLEX® Tee supplied.
Flex Ready Rigid Tee also available.



Dripless Type "A" Connector

Part No.: 2CNNTRC

Dia.: _____

Dia.: 3" – 24"

Used to mate Z-FLEX® Liner to stove-pipe or when going through a fireplace insert.



Nose Cone

Part No.: 2NCXXX

Dia.: _____

Dia.: 3" – 24"

To attach to liner, attach rope to cone and pull rope down chimney.



Reducer/Increaser

Reducer Part No.: 2RD

(Dia)R: _____ (Dia)X: _____

Increaser Part No.: 2IN

(Dia)R: _____ (Dia)X: _____

Dia.: 3" – 24"



Insulating Blanket w/Wrap & Gear Clamps

Part No.: 2INSKIT

Dia.: _____

Includes 2 gear clamps per 5' section.