



OUTDOOR
FIREPLACES



Terrazza



Terrazza XL



Loke



Frøya

FEATURES

- Made from 14 gauge (sides) and 11 gauge (bottom) COR-TEN® steel.
- COR-TEN® steel resists the corrosive effects of rain and snow by forming a coating of oxidation over the metal. This patina layer changes over time from light orange-brown to a deep rich dark brown. This coating not only makes each fireplace look unique, but helps protect the steel, allowing the fireplace to be left outside all year round.

OPTIONS

- Spark Screen
- Grill Kit (Terrazza, Terrazza XL, Loke only)



Before oxidation



After oxidation



Terrazza (Weight: 66 lbs)
46 1/2"H x 15 3/4"D x 15 3/4"W



Frøya (Weight: 45 lbs)
57 1/2"H x 23"D x 23"W



Loke (Weight: 92 lbs)
58 1/4"H x 15 3/4"D x 15 3/4"



Terrazza XL (Weight: 106 lbs)
63"H x 22"D x 22"W

- For outdoor use only.
- The fireplace should be located on a firm, non-combustible surface such as a brick, stone, or concrete patio.
- Outdoor fires should be located away from any adjoining property lines and 60 inches from any combustible structure or material. Combustible structures include dwellings, garages, sheds, decks and fences.
- Only seasoned firewood should be used as fuel for outdoor fires.

TIMELESS NORWEGIAN CRAFT

